

POWER SUPPLY RSP-2000-12



TECHNICAL SPECIFICATION		
ITEM	FEATURE	CAPACITY
1	OUTPUT CURRENT (MIN.-MAX.)	0 - 100 [A]
2	INPUT VOLTAGE (MIN.-MAX.)	90 - 264 [VAC]
3	OUTPUT VOLTAGE (MIN.-MAX.)	14 - 12 [VDC]
4	CONNECTION	Screw terminals
5	DIMENSION (L x W x H)	295 x 127 x 41 [mm]
6	WEIGHT	2116,67 [g]

POWER SUPPLY RSP-3000-24



TECHNICAL SPECIFICATION		
ITEM	FEATURE	CAPACITY
1	OUTPUT CURRENT (MIN.-MAX.)	0 - 125 [A]
2	INPUT VOLTAGE (MIN.-MAX.)	180 - 264 [VAC]
3	OUTPUT VOLTAGE	24 [VDC]
4	CONNECTION	Screw terminals
5	DIMENSION (L x W x H)	278 x 177,8 x 63,5 [mm]
6	WEIGHT	4000 [g]

POWER SUPPLY MDR-20-24



TECHNICAL SPECIFICATION		
ITEM	FEATURE	CAPACITY
1	OUTPUT CURRENT (MIN.-MAX.)	0 - 1 [A]
2	INPUT VOLTAGE (MIN.-MAX.)	90 - 264 [VAC]
3	OUTPUT VOLTAGE	24 [VDC]
4	CONNECTION	Din Rail
5	DIMENSION (L x W x H)	22,5 x 90 x 100 [mm]
6	WEIGHT	190,28 [g]

All rights reserved by iSiNitzan. Reproduction and distribution of any part of this document is prohibited.



POWER SUPPLY MDR-60-24



ITEM	TECHNICAL SPECIFICATION	
	FEATURE	CAPACITY
1	OUTPUT CURRENT (MIN.-MAX.)	0 - 2,5 [A]
2	INPUT VOLTAGE (MIN.-MAX.)	90 - 264 [VAC]
3	OUTPUT VOLTAGE	24 [VDC]
4	CONNECTION	Din Rail
5	DIMENSION (L x W x H)	40 x 90 x 100 [mm]
6	WEIGHT	333,33 [g]

POWER SUPPLY DRA-60-24



ITEM	TECHNICAL SPECIFICATION	
	FEATURE	CAPACITY
1	OUTPUT CURRENT (MIN.-MAX.)	0 - 2,5 [A]
2	INPUT VOLTAGE (MIN.-MAX.)	90 - 264 [VAC]
3	OUTPUT VOLTAGE	24 [VDC]
4	CONNECTION	Din Rail
5	DIMENSION (L x W x H)	100 x 90 x 400 [mm]
6	WEIGHT	300 [g]

POWER SUPPLY WDR-120-24



ITEM	TECHNICAL SPECIFICATION	
	FEATURE	CAPACITY
1	OUTPUT CURRENT (MIN.-MAX.)	0 - 5 [A]
2	INPUT VOLTAGE (MIN.-MAX.)	180 - 550 [VAC]
3	OUTPUT VOLTAGE	24 [VDC]
4	CONNECTION	Din Rail
5	DIMENSION (L x W x H)	40 x 125 x 113,5 [mm]
6	WEIGHT	650 [g]

All rights reserved by iSiinitzan. Reproduction and distribution of any part of this document is prohibited.



POWER SUPPLY WDR-240-24



ITEM	TECHNICAL SPECIFICATION	
	FEATURE	CAPACITY
1	OUTPUT CURRENT (MIN.-MAX.)	0 - 10 [A]
2	INPUT VOLTAGE (MIN.-MAX.)	200 - 550 [VAC]
3	OUTPUT VOLTAGE	24 [VDC]
4	CONNECTION	Din Rail
5	DIMENSION (L x W x H)	63 x 125 x 113,5 [mm]
6	WEIGHT	650 [g]

POWER SUPPLY TDR-240-24



ITEM	TECHNICAL SPECIFICATION	
	FEATURE	CAPACITY
1	OUTPUT CURRENT (MIN.-MAX.)	0 - 10 [A]
2	INPUT VOLTAGE (MIN.-MAX.)	340 - 550 [VAC] - 3 PHASE
3	OUTPUT VOLTAGE	24 [VDC]
4	CONNECTION	Din Rail
5	DIMENSION (L x W x H)	113,5 x 63 x 125,20 [mm]
6	WEIGHT	1000 [g]

POWER SUPPLY SDR-960-24



ITEM	TECHNICAL SPECIFICATION	
	FEATURE	CAPACITY
1	OUTPUT CURRENT (MIN.-MAX.)	0 - 40 [A]
2	INPUT VOLTAGE (MIN.-MAX.)	180 - 264 [VAC]
3	OUTPUT VOLTAGE	24 [VDC]
4	CONNECTION	Din Rail
5	DIMENSION (L x W x H)	110 x 125 x 150 [mm]
6	WEIGHT	1000 [g]

All rights reserved by iSiinitzan. Reproduction and distribution of any part of this document is prohibited.



POWER SUPPLY TDR-480-24



TECHNICAL SPECIFICATION		
ITEM	FEATURE	CAPACITY
1	OUTPUT CURRENT (MIN.-MAX.)	0 - 20 [A]
2	INPUT VOLTAGE (MIN.-MAX.)	340 - 550 [VAC]
3	OUTPUT VOLTAGE	24 [VDC]
4	CONNECTION	Din Rail
5	DIMENSION (L x W x H)	128 x 85,5 x 1125,2 [mm]
6	WEIGHT	1560 [g]

