

## HYDROSTATIC SUBMERSIVE PRESSURE TRANSMITTER



ITEM	FEATURE	TECHNICAL SPECIFICATION	
		CAPACITY	
		PS3208	PS3407
1	OUTPUT SIGNAL	Analog Signal (4 to 20 [mA])	
2	MEASURING RANGE	0 to 0,25 [bar]	0 to 0,6 [bar]
		0 to 250 [mbar]	0 to 600 [mbar]
		0 to 3,63 [psi]	0 to 8,7 [psi]
		0 to 25 [kPa]	0 to 60 [kPa]

## FLUSH PRESSURE SENSOR PM1608



ITEM	FEATURE	TECHNICAL SPECIFICATION	
		CAPACITY	
		PM1608	PM1689
1	OUTPUT SIGNAL (CONFIGURABLE)	Analog signal (4 to 20 [mA]) IO-Link	
2	PROCESS CONNECTION	Threaded connection (G 1) External thread (Sealing core)	
3	MEASURING RANGE	-0,0125 to 0,25 [bar]	-0,005 to 0,1 [bar]
		- 12,5 to 250 [mbar]	- 5 to 100 [mbar]
		-0,182 to 3,626 [kPa]	-0,073 to 1,45 [psi]
		-1,25 to 25 [MPa]	-0,5 to 10 [kPa]

