



Profine® ZERO

Your finest water at home

Profine® **ZERO** offers in one product:

- Faucet with filter change alarm (smart tap)
- High instantaneous flow
- No electricity required
- Quiet and compact



DIMENSIONS			
CODE	WIDTH	DEPTH	HEIGHT
S0ZR0020-ALX - ZERO ITA	360 mm	360 mm	150 mm
S0ZR0020-ALP - ZERO ENG	360 mm	360 mm	150 mm

PACKAGING		
WIDTH	DEPTH	HEIGHT
383 mm	390 mm	197 mm

TECHNICAL SPECIFICATIONS	
Instantaneous flow rate	3 l/min
min/max operating pressure	1,5 bar - 6 bar
min/max temperature	5°/35° C
Pre-Post filtration	CB AG 0,5 MS Profine® Carbon Block
Capacity filters	7.000 l



Profine® ZERO

LIGHT WATER FROM YOUR TAP

SMALL SPACE, GREAT PERFORMANCE

SILENT AND ELECTRICITY FREE

ZERO is a patented osmosis system made in a compact form, including pre-treatment and post-treatment with bacteriostatic action capable of producing osmotic water with instantaneous high flow rate. The exclusive design features housings of disposable filters in an easily accessible ergonomic compartment for ordinary and extraordinary maintenance operations, with the total absence of traditional hydraulic connections for an integrated circuit.

With ZERO something extraordinary was born that revolutionizes our way of drinking tap water. Rising from the will to be radical and dismantle the old logic of the water treatment industry, ZERO gives light water technology to be no longer a cold and technical subject but thought around us and our home life.

The under-sink world is often a labyrinth rich in objects and poor in space. We wanted to enclose in less than one briefcase the technology to give you much good, safe, and light drinking water. We do this by renouncing all those classic elements that the current systems of this type need to have to not diminish their flow rates, first of all the outer tank, all this by enhancing the performances.

Our greatest effort was to satisfy the need to create the system to have light water able to work without making any noise unless the water runs. ZERO also wanted to respond to another need, that is, the total safety in use, eliminating all possible electrical connections. ZERO does not have pump or motor, to install it just connect it to your home water system.



Profine® ZERO

Your finest water at home



Temperature
Min 5 – Max 35° C



Operating pressure
Min 1,5 bar - Max 6 bar



ZERO WATER LABEL

PARAMETER (with by-pass off)		IN	OUT
conductivity at 77 °F	µS/cm	289	14,7
hydrogen ion concentration	pH	8,15	7,54
chloride	mg/l	3,1	0,223
solphates	mg/l	19,3	0,572
zinc	µg/l Zn	11,8	n.r.
calcium	mg/l Ca	32,4	1,48
magnesium	mg/l Mg	11,5	0,45
potassium	mg/l K	0,7	0,176
sodium	mg/l Na	2,07	0,52
total phosphorus	µg/l P ₂ O ₅	29,8	n.r.
hexavalent chromium	µg/l Cr	0,94	n.r.
nitrates	mg/l	3,5	2,9
pfas	ng/l	250	0,0

TECHNICAL DATA

INLET PRESSURE	CAPACITY SUPPLIED IN 1 MINUTE	REFILL TIME
2,5/36 bar/PSI	2,4 litri	18 min
3/43 bar/PSI	2,7 litri	14 min
4/58 bar/PSI	3 litri	10 min

TEST CONDITIONS

rejection	> 90 *
recovery (typically at a pressure of 3 PSI)	40 % *

* variable depending on the temperature and the quality of the incoming water

INSTALLATION

ZERO can be mounted in a vertical or horizontal position.
For installation, follow the local regulations in force and the instructions of the equipment.

REPLACEMENT

Replace the cartridges no later than 12 months from the date of installation.
Replace the LED indicator battery every time you replace the cartridge.

COMPANY CERTIFICATIONS

Made in Italy by think:water, an ISO 9001-2015 certified company (quality)
and ISO 14001-2015 (environment).

PRODUCT CERTIFICATIONS

Complies with **ICIM, DM25/2012 Compasso d'oro, IF Design Award 2016**
Gold Seal Certificate NSF and **TIFQ LAB** regulations.

ENVIRONMENT

Dispose of the used cartridge according to Decision 2000/532/EC
(CER code 15 02 03)